# MATERIAL SAFETY DATA SHEET

MANUFACTURERS' NAME: ADVANCED COATINGS & CHEMICALS

Subsidiary of Olin Hunt Specialty Products, Inc.

DATE OF PREPARATION:

9-19-86

4343 Temple City Blvd. Temple City, CA 91780

EMERGENCY PHONE NO: (818) 579-6270

SECTION	I-PRODUCT	IDENTIFICATION

PRODUCT FORMULA:

3-1W-21

PRODUCT NAME:

----

URAFILM TFE WHITE DN 7622

PRODUCT CHEMICAL FAMILY:

POLYTETRAFLOURD ETHYLENE

PRODUCT CHEMICAL FAMILY:	POLYTETRAFLO				
	SECTION II—	HAZARDOUS INC	SREDIENTS		
	CAS NUMBER	EXPOSURE LIMITS IN AIR		IARC, NTP OSHA HAZARD	
INGREDIENTS		OSHA PEL	ACGIH TLV	EVALUATION	
POLYTETRAFLOURD ETHY	LENE 9002-84-0	15mg/m³	10mg/m³	NON-CARCINOGENIC	
EPOXY	25068-38-6	5 ppm	2 ppm	EPICHLORHYDRIN-CARCII EN IARC Vol.2 Page 1	
AZELAIC ACID	123-99-9	Not Est.	Not Est.	NON-CARCINOGENIC	
TITANIUM DIOXIDE	1314-13-2	15 mg/m³	5mg/m³	NON-CARCINOGENIC	
BARYTES	7727-47-7	15mg/m³	10mg/m³	NON-CARCINOGENIC	
ALUMINA	1344-28-7	5 mg/m³	10 mg/m³	NON-CARCINOGNEIC	
ETHYL 3-ETHOXY ROPIONATE	763-69-0	Not Est.	Not Est.	NON-CARCINOGENIC IRRITANT; MILDLY TOXI	
METHYL NORMAL AMYL KETONE	110-43-0	100 ppm	100 ppm	NARCOTIC NON-CARCINOGENIC	
METHYL ETHYL KETONE	78-93-3	200 ppm	200 ppm	NON-CARCINOGENIC NARCOTIC	
			·		
	SECTIO	ON III—PHYSICAL	_ DATA		
POILING POINT:	175°F	SPECIF	FIC GRAVITY:	1.21	
BOILING POINT:			ATILE BY VOLUME: _	56%	
VAPOR DENSITY (AIR = 1): HEAVIER SOLUBILITY IN WATER: NEGLIGIBLE	EVAPORATION RATE:		OT OLITE		
VAPOR PRESSURE: @20°C	70	mm.Hg.	L ACETATE = 1)		
	SECTION IV-FIRE	E AND EXPLOSI	VE HAZARD DAT/	A	
20				10.0	
FLASH POINT: 20	OF, TCC_LEL:	1.05	% by Volume_UEL	<u>: 10.0 %</u>	

EXTINGUISHING MEDIA: Foam, Dry Chemical, CO<sup>2</sup> and/or Water Fog UNUSUAL FIRE AND EXPLOSION HAZARDS:

During a fire, irritating and toxic gases and smoke are present from decomposition. Isolate from heat, sparks and open flames. Closed containers may burst when exposed to extreme heat. Vapors form an explosive mixture in air between the upper and lower explosive limits.

SPECIAL FIREFIGHTING PROCEDURES: Full emergency equipment with self-contained breathing apparatus should be worn by firefighters.

## SECTION V—HEALTH HAZARD DATA

#### **EFFECTS OF ACUTE OVEREXPOSURE:**

Eyes: Can cause severe irritation, redness, tearing and blurred vision. Skin: Prolonged or repeated contact can cause irritation. Defatting to skin.

Inhalation: Dizziness, breathing difficulty, headaches and loss of coordination.

Ingestion: Damage to throat and esophagus, vomitting and diarrhea.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Asthma, respiratory tract irritation, dermatitis. Kidney and liver problems, conjunctivitis.

PRIMARY ROUTES OF ENTRY: Dermal, inhalation, ingestion.

#### **EMERGENCY AND FIRST AID PROCEDURES:**

Eye Contact: Flush with large amounts of water for 15 minutes.

Skin Contact: Wash thoroughly with soap and water. See a doctor

Inhalation Over Exposure: Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention.

Ingestion: Do not induce vomitting. Can cause chemical pneumonitis and pulmonary edema. Contact physician immediately.

# OTHER HEALTH HAZARDS: EFFECTS OF CHRONIC OVEREXPOSURE:

EYES: Blurred vision. Conjuctivitis. SKIN: Sensitization, dermatitis. INHALATION: Asthma-like symptoms. Central nervous system effects. INGESTION: Damage to throat. Possible kidney and liver impairment.

# SECTION VI—REACTIVITY DATA

#### **STABLITY:** Stable

RDOUS POLYMERIZATION: Will not occur.

## HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide; carbon dioxide, oxides of nitrogen, various hydrocarbon and acrid fumes.

### **CONDITIONS TO AVOID:**

Excessive heat, poor ventilation. Corrosive atmosphere, excessive aging, sparks and open flames.

# INCOMPATIBILITY (MATERIAL TO AVOID):

Alkaline materials, strong acids and oxidizing materials.

# SECTION VII—SPILL OR LEAK PROCEDURES

# STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate ignition sources; provide good ventilation; dike spill area and add absorbent material to spilled liquid. Thoroughly wet with water and mix.

#### WASTE DISPOSAL METHOD:

Collect absorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local, state and federal hazardous waste regulations before disposing into approved hazardous wastes landfills. Obey relevant laws.

SECTION VIII-	SAFF	HANDL	ING	AND	USE	INFORM	IATIO	١N
---------------	------	-------	-----	-----	-----	--------	-------	----

# RESPIRATORY PROTECTION:

When spraying and/or printing this material, use a NIOSH-approved cartridge respirator or gas mask suitable for airborne mists and vapor concentrations below the time-weighted threshold limit values. When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.

#### **VENTILATION:**

General mechanical ventilation or local exhaust should be suitable to keep vapor concentration below TLV. Ventilation equipment must be explosion-proof.

PROTECTIVE GLOVES: Impermeable chemical handling gloves for skin protection.

EYE PROTECTION: Use chemical safety glasses, goggles and face shields for eye protection.

# OTHER PROTECTIVE EQUIPMENT:

Use impermeable aprons and protective clothings when ever possible to prevent skin contact. The use of head caps when ever possible is strongly recommended.

HYGIENIC PRACTICE: Eye washes and safety showers in the work palce is recommended.

# SECTION IX—SPECIAL PRECAUTIONS

# PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Use non-sparking utensils when handling this material. Avoid hot metal surfaces. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.

Smoking in areas where this material is used should be strictly prohibited. Tools used with this material should be aluminum, brass or copper. Plastic tools should not be used. Since emptied containers retain product residues, (vapors, liquid and/or solid) all hazard precautions should

COLUMN TO SERVICE STATE OF THE PERSON STATE OF					
		SECTION	X-TRANSPORTATION	ON DATA	
	PRINC NAME	PAINT UN	1263		
PROPER SE	IIPPING NAME:	seperate ways of seq.		DED SECTION	
DOT CLASS	SIFICATION:	LAMMABLE	DOT LA	BEL: RED	

PRECAUTIONS TO BE TAKEN IN TRANSPORTATION: NOTE: THIS INFORMATION IS ACCURATE TO THE BEST KNOWLEDGE OF ADVANCED COATING & CHEMICALS COMPANY, BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.

Refer to Section IX